

TECHNICAL DATA SHEET

PERMASTOP® BUILDING BLANKET REFLECTIVE THERMAL & ACOUSTIC INSULATION BLANKET

Product description and typical applications

Permastop® Building Blanket is a reflective insulation composite comprising of a glasswool blanket substrate that is faced on one side with a high quality Sisalation® reflective foil laminate. For ease of installation, the reflective foil laminate features a 150mm overlap along one side edge.

Australian made Permastop® Building Blanket is suitable for use in residential and commercial metal clad roof applications as well as metal clad walls. It provides excellent thermal and acoustic properties by reducing heat loads entering a building and minimising the internal reverberation and flow of unwanted nuisance noise generated from adjacent buildings/rooms and/or the external environment. Additionally, the Sisalation® reflective foil component of Permastop® Building Blanket aids in minimising the risk of condensation that can form in a metal clad roof.


Where the foil surface of Permastop® Building Blanket is required to maintain a vapour barrier, all joins should be sealed with a suitable Fletcher Insulation tape. Permastop® Building Blanket is typically installed with the reflective surface facing downwards into the air-space below; except in hot and humid tropical regions where the reflective foil is typically installed on the underside of the metal roof sheet. In such conditions, where the building blanket is used in an exposed application, Fletcher Insulation recommends installing the blanket as per standard procedures and running an additional layer of anti-glare foil laminate atop the blanket towards the metal roof sheet. This allows for an enhanced aesthetic finish.

Permastop® Building Blanket is suitable for use in bushfire areas with a Bushfire Attack Level (BAL) of 0 – 40 in accordance with AS 3959-2009. Note: where aesthetics is of critical importance, Fletcher Insulation recommends installing the foil layer separately followed by the glasswool building blanket.

Physical characteristics

Foil Facing Type	Material R-value m²K/W	Nominal thickness mm	Width mm	Length m	m² per roll	Product code
Sisalation® Light Duty (LD) reflective foil laminate Group no. 1 AS5637*	R1.3	55	1200	15	18.00	912150
	R1.3	55	1200	20	24.00	912200
	R1.4	60	1200	15	18.00	910150
	R1.4	60	1200	20	24.00	910200
	R1.8	75	1200	15	18.00	913150
	R1.8	75	1400	15	21.00	912075
	R2.0	90	1200	15	18.00	914162
	R2.3	100	1200	10	12.00	914163
	R2.5	100	1200	10	12.00	914100
	R3.0	130	1200	10	12.00	930100
	R3.2	130	1200	10	12.00	930101
	R3.6	130	1200	6.5	7.80	930360
Sisalation® Medium Duty (MD) reflective foil laminate Group no. 2 AS5637*	R1.3	55	1200	15	18.00	917150
	R1.4	60	1200	15	18.00	910151
	R1.8	75	1200	15	18.00	918150
	R2.3	100	1200	10	12.00	911471
	R2.5	100	1200	10	12.00	919100
	R3.0	130	1200	10	12.00	931100
	R3.2	130	1200	10	12.00	930201
	R3.6	130	1200	6.5	7.80	930362
Sisalation® Heavy Duty (HD) reflective foil laminate Group no. 2 AS5637*	R1.3	55	1200	15	18.00	927150
	R1.4	60	1200	15	18.00	910152
	R1.8	75	1200	15	18.00	928150
	R2.3	100	1200	10	12.00	928163
	R2.5	100	1200	10	12.00	929100
	R3.0	130	1200	10	12.00	932100
	R3.2	130	1200	10	12.00	930301
	R3.6	130	1200	6.5	7.80	930364

*AS5637.1:2015: Determination of fire hazard properties - Wall and ceilings



*In accordance with AS 3959-2009 Construction of Buildings, Alterations and Additions in Bushfire Prone Areas

Fletcher Spec^{pro}
www.insulation.com.au/fletcherspecpro

Fletcher
Insulation
Building Better, Together.

Thermal performance

Permastop® Building Blanket complies with the requirements of AS/NZS 4859.1:2002 including Amendment 1. The thermal performance of Permastop® Building Blanket varies with application and installation method. For complete Total R-value guidance visit www.insulation.com.au/fletcherspecpro

Bushfire Attack Level (BAL)

Permastop® Building Blanket is suitable for use in bushfire areas with a Bushfire Attack Level (BAL) of 0 - 40 as outlined in AS 3959. The glasswool component of Permastop® Building Blanket is classified as non-combustible in accordance with AS 1530.1 and is suited for sealing ember entry points at ridges, valleys and fascias to meet NCC requirements for metal clad roofs in bushfire areas. The Sisalation® reflective foil facing component satisfies the NCC flammability index requirement of ≤ 5 .

Early fire hazard properties

Permastop® Building Blanket achieves the following results when tested in accordance with AS1530.3-1999:

Ignitability Index	0
Spread of Flame Index	0
Heat Evolved Index	0
Smoke Developed Index	0-1

Maximum service temperature

Permastop® Building Blanket is manufactured for use at temperatures that are normally experienced in building systems. The maximum surface temperature of the glasswool substrate is 340°C. However, given a foil facing is applied to the substrate; the surface temperature of Permastop® Building Blanket should not exceed 70°C.

Moisture absorption

Permastop® Building Blanket absorbs less than 0.2% moisture by volume when exposed to environmental conditions of 50°C and 95% relative humidity for four days.

Alkalinity

When tested in accordance with British Standard 3958, Fletcher Insulation™ glasswool products receive a rating of pH9 (pH7 is neutral). They will not promote or accelerate the corrosion of steel or galvanised steel studs provided they are protected from external contamination.

Safe to use

Permastop® Building Blanket is manufactured from FBS-1 Glasswool Bio-Soluble Insulation®. FBS-1 Glasswool Bio-Soluble Insulation® is safe to use and meets the criteria of the Australian Safety and Compensation Council (formerly NOHSC) to be classified as non-hazardous. Fletcher Insulation™ glasswool can be used with confidence in any residential, commercial or industrial application.

Green Star compliant

Fletcher Insulation avoids the use of Ozone Depleting Potential (ODP) substances in the manufacture or composition of its FBS-1 Glasswool Bio-Soluble Insulation® and Sisalation® reflective foil products.

The use of Permastop® Building Blanket guarantees the use of Zero ODP insulation while also ensuring that no harmful levels of Volatile Organic Compounds (VOC's) are released. This allows the incorporation of environmentally preferable insulation whilst also maintaining indoor air quality.

Specification notes

The insulation material shall be Fletcher Insulation Permastop® Building Blanket ____ (specify foil duty rating i.e. LD, MD or HD) with a Material R-value of R ____ m²K/W (specify Material R-value) at a nominal thickness of ____ mm (specify nominal thickness).

© Fletcher Insulation Pty Limited 2018. Fletcher Insulation reserves the right to change product specifications without prior notification. Information in this publication and otherwise supplied to users as to the subject product is based on our general experience and is given in good faith, but because of the many particular factors which are outside our knowledge and control and affect the use of products, no warranty is given or is to be implied with respect to either such information or the product itself, in particular the suitability of the product for any particular purpose. The purchaser should independently determine the suitability of the product for the intended application. Unless otherwise stated all ™ and ® are trademarks and registered trademarks of Fletcher Insulation Pty Limited ABN 72 001 175 355.
HTDS1_Revision_2_Issue Date 05062018



Ceilings, Walls & Partitions
(08) 8292 5000
www.adxdepot.com.au

Fletcher
Insulation
Building Better, Together.