



**soundshield** can be used to create peaceful environments at work and home.

## soundshield

### performance plasterboard



**soundshield** is a plasterboard with a high density core for systems where superior sound insulation performance is required. **soundshield** has recycled yellow liner paper.

### application

**soundshield** is used in a wide range of residential and commercial applications such as home theatres, media rooms and confidential meeting rooms where reducing sound transmission from one room to another is the primary concern. **soundshield** can be installed on ceilings and wall partitions to provide quieter living and working conditions.

**soundshield** can be used within systems that require certified plasterboard to achieve 100% points in the relevant categories for Green Star projects.

### key benefits

- superior acoustic performance
- reduces transfer of sound between rooms to improve indoor environment quality
- easy and economical to install compared with brick work and masonry
- certified for use in Green Star projects



## product information

	thickness(mm)	width (mm)	length (mm)			weight* (kg/m <sup>2</sup> )
			3000	3600	6000	
sheet size	10*	1200/1350		•	•	8.4
	13	1200	•			12.3
fire hazard properties	Group 1 with an Average Specific Extinction Area <250 m <sup>2</sup> /kg determined in accordance with AS 5637.1 as required by NCC C1.10, Clause 4.					
combustibility	May be used wherever a non-combustible material is required according to the Building Code of Australia (BCA) C1.9 (e)					
hazards identification	Non-hazardous according to WHS Regulations and the ADG Code					

\* Weights indicated are nominal. Minimum order quantities and lead times may apply.

## performance

### Sound

Systems with **soundshield** can achieve very high levels of sound insulating performance. The sound insulating effectiveness of walls depends on their  $R_w$  values. Table 1 shows the effects of various sound insulation ratings. Refer to the latest Siniat Literature or system selector on the website for systems with acoustic ratings.

#### R<sub>w</sub> and R<sub>w</sub> + C<sub>tr</sub> Definitions:

##### R<sub>w</sub> - Weighted Sound Reduction Index

$R_w$  describes the airborne sound insulating performance of a building element. It is a laboratory measured value. It can apply to walls, ceiling/ floors, ceiling/roofs, doors or windows. The higher the number, the greater the sound insulating performance of the building element. For example, an increase in the  $R_w$  of a wall by 10 points will reduce the perceived loudness of sound passing through the wall by about half.

**Sustainable** Green Star compliance documents are available at [www.siniat.solutions/certificates](http://www.siniat.solutions/certificates). **soundshield** can be used within systems that require certified plasterboard to achieve 100% points in the relevant categories for Green Star projects.

### Sound installation performance

Table 1.

R <sub>w</sub>	effect of different values of R <sub>w</sub> on sound insulation performance
25	Normal speech can be heard easily
30	Loud speech can be heard easily
35	Loud speech can be heard but not understood
42	Loud speech heard as murmur
45	Must strain to hear loud speech
48	Loud speech can be barely heard
53	Loud speech can not be heard
63	Music heard faintly, bass notes 'thump'
70	Loud music still heard very faintly



Quality  
ISO 9001



All Siniat products have been developed to meet the specific needs of the Australian market. Products manufactured in Australia comply with quality systems certified as complying with AS/NZS ISO 9001:2008 and meet the requirements of AS/NZS 2588, Gypsum Plasterboard.



The following Siniat products have been independently certified by Global GreenTag to GreenRate Level A: **mastashield**, **fireshield**, **fireshield h**, **soundshield**, **watershield**, **spanshield**, **multishield**, **curveshield**, **opal**, **trurock** and **trurock hd**. Compliance certificates are available on [siniat.com.au](http://siniat.com.au).



All Siniat plasterboard and metal products are available on the Siniat Carbon Neutral Opt-In program to help you meet your sustainability goals. Visit [siniat.com.au](http://siniat.com.au) to find out more.

#### Disclaimer

Products manufactured and systems designed by Etex Australia Pty Ltd and branded Siniat, are produced in accordance with the Building Code of Australia and relevant Australian Standards. Information in this document is to be used as a guide only and is subject to project approval as many aspects of construction are not comprehensively covered. It is also the responsibility of the project to determine if Siniat's products and systems are suitable for the intended application. Etex Australia Pty Ltd will not be held responsible for any claims resulting from the installation of its products or other associated products not in accordance with the recommendations of the manufacturer's technical literature or relevant Australian Standards. Siniat technical information is regularly updated. To ensure this document is current with the latest information, visit [siniat.solutions](http://siniat.solutions)

#### Siniat.solutions provides a host of online solutions for your product

#### **siniat SELECT**<sup>®</sup>

offers an online system selector and custom design specification proposal, developed by us and catered to your project's requirements.

#### **siniat CALCULATE**<sup>®</sup>

is a range of online calculation tools for the professional. Explore [siniat.solutions](http://siniat.solutions) on [siniat.com.au](http://siniat.com.au).



**Etex Australia Pty Ltd**

ABN 61 003 621 010  
31 Military Road, Matraville  
NSW 2036

[siniat.com.au](http://siniat.com.au)



#### warranty

Siniat's products are guaranteed by a 10 Year Warranty. For details visit [siniat.com.au](http://siniat.com.au)

technical advice  
**AU 1300 724 505**